



## Dexter lifts have been manufactured in Finland for almost 40 years

Dexter trailer lifts are suitable for a wide range of applications. The small total weight and large reaches allow it to be used even in demanding places. Four independently adjustable support legs make it easier to level the lift, even on uneven and sloping surfaces. Continuous boom rotation and standard drive provide access to tight spaces. Thanks to the strong and sturdy frame, towing the lift is effortless and the long distances between work sites are not a problem.

All Dexter lifts are made of highstrength steel at our own factory in Nokia and are light but sturdy in relation to their lifting height. The products are designed for demanding operating conditions, with the goal of operational reliability and operational safety in particular. All crane service points are easily accessible and the joints are equipped with lubrication nipples. All components prone to damage are protected by metal guards.



The 15Z telescopic boom allows you to work at heights of up to 15 meters, but weighs only 1 500 kg. An excellent choice when workplaces are high and change frequently. With the optional petrol engine unit, you can work effortlessly even where no mains power is available.



MAX WORKING HEIGHT 15.0 m



MAX PLATFORM HEIGHT 13.0 m



OUTREACH 6,5 m / 215 kg, 8,0 m / 120 kg



WORKING WIDTH 4,0 m



MAX LOAD 215 kg / 2 people



PLATFORM SIZE (I x w x h) 0,8 m x 1,25 m x 1,1m



PLATFORM ROTATION +/-40°



BOOM ROTATION continuous



PUOMILIIKKEIDEN HALLINTA 2-speed, proportional (optional)



MACHINE LENGTH 6.7 m



MACHINE WIDTH 1.8 m



MACHINE HEIGHT 2.1 m



MACHINE WEIGHT 1500 kg



STANDARD POWER SOURCE 230V / 50 Hz / 1,9 kW electric motor



PETROL ENGINE optional



TRACTION DRIVE standard



GRADEABILITY 15 %



